

Walk-In Products that Comply with The Energy Independence and Security Act

Hardware and Vinyl Curtains



1346 Performer Adjustable Hinge



1096L and 1096M Adjustable Door Closers



27C Handle with Low Conduction 1/4 Turn Inside Release



58 SafeGuard® Radial Latch



1094 Hydraulic Door Closer



Easimount® Strip Curtains



Thermal Flex® Swing Doors



LED Lighting and Accessories



1810LCT400 LED



1810LC4000-B LED (90-min Battery Backup)



1809 LED



1808 LED



1808NMA



1808FMA



1901A Motion Sensor



1802 LED Safety Light



1826 Intelli-Vent®



Kason Helps Reduce Your Utility Costs

1346 Performer Adjustable Hinge

- Easily adjustable strap provides lift and rotation to compensate for door sag
- Cam-rise technology assists closing and reduces gasket wear
- 40% more rise than traditional cam-rise hinges

1096L & 1096M Adjustable Door Closers

- Saves energy by helping doors close from dwell position
- Works with cam-rise and standard hinges
- Designed for left or right handed installations
- Easily mounts to existing doors and adjusts with standard tools

1094 Hydraulic Door Closer

- Ensures solid closure of doors
- Extra-wide hook eliminates alignment problems
- Easily adjust to compensate for door sag
- Bend-resistant hook assures long wear in heavy use

58 SafeGuard® Radial Latch

- Releases with minimum pressure
- Reliable, self-closing action provides air tight closure

27C Deadbolt Handle Latch

- Deadbolt security for walk-ins at the economy of a locking pull handle
- Compare total cost and function of this patented deadbolt latch

27C 1/4 Turn Low Conduction Inside Release

- Prevents entrapment in walk-in coolers and freezers
- Meets ADA requirements for emergency egress
- Large glow-in-the-dark surface provides better visibility in low-light or emergency situations
- Includes alignment plate for outside strike to maintain proper alignment in field
- Tethered connection included for outside strike lock mechanism

Easimount® Vinyl Strip Curtains

- Features precreated slide-in strips for quick mounting and removal
- Patented mounting system prevents tear-out
- Custom sizes available upon request

Thermal Flex® Vinyl Swing Doors

- Gravity hinge closes door quickly and gently
- Adjustable cam block assures door swings back to center position
- 10-year rust-proof hinge warranty

1810LCT400 LED Fixture

- IP-65 dimmable energy-efficient lighting
- Surface mounting brackets
- High-impact resistant polycarbonate enclosure
- Designed for walk-in coolers/freezers
- Operating temp -40°F to 104°F (-40°C to 40°C)
- Rated 50,000+ hours of life

1810LC4000-B LED Fixture with Backup Battery

- 90-minute battery backup for walk-in cooler/freezers down to 32°F (0°C)
- Universal input voltage, 40 W total
- High-impact resistant polycarbonate enclosure
- Pre-installed surface mount LED strips
- Easily retrofit inefficient lighting
- Mercury free, LM-79 tested, LM-80 tested
- Rated 50,000 hour life

1809 LED Fixture

- 3450 lumens, 4000k color temperature
- Compact size, yet offers up to same lumens as 4 ft. fixtures
- Low profile, high impact Lexan globe with anti-glare technology
- Easily retrofit inefficient lighting
- Designed to reduce lighting electrical usage by 85%
- Minimal heat generation helps lower utility costs

1808 LED Fixture

- 120 or 240 V, 50/60 Hz
- 1355 lumens, 4000k color temperature
- Designed to reduce lighting electrical usage by 85%

1808NMA/1808FMA LED Fixtures

- 120 or 240 V, 50/60 Hz
- 1480+ lumens, 4000k color temperature
- Designed to reduce lighting electrical usage by 85%

1901A Motion Sensor

- Turns lights on only when area is in use
- Extends life of light fixtures
- Reduces heat in freezers and coolers

1802 LED Safety Light

- Safe "Always-ON" 100 lumen illumination
- Small size can be mounted almost anywhere
- Easy to install/retrofit into new and existing fixtures
- 4000K color temperature, 1 W, 120 V
- Threads into 1/2" NPT conduit or mounts in 7/8" diameter hole

1826 Intelli-Vent(R) Pressure Relief Port, Safety Light and Multi-Optional Junction Box

- "Always-ON" LED safety light provides energy-efficient security
- Dual chambered vent allows doors to open/close easier
- LED doubles as heat source to prevent ice buildup and reduce service calls
- Junction box offers power access from the front of unit, or addition of motion sensor