

# 0488L Panic Bar Inside Release and Latch Assembly (UL 305 Certified)

Part Number: 10488L\*



U.S. Patent No. 11,193,311

## FEATURES

- UL305 and Can/ULC-S132 certified panic device
- Stainless steel and aluminum materials for non-corroding construction
- Crossbar design provides a large contact area for opening door
- Ergonomic design provides simple low-effort operation
- Accommodates left and right handed doors

## MATERIALS

- **Cross bar:** 304 stainless steel
- **Mounting brackets:** 304 stainless steel
- **Push rod:** 303 series stainless steel
- **Cover:** Die-cast aluminum
- **Pivot arm:** Die-cast aluminum
- **Hardware:** Stainless steel
- **Pin:** 304 stainless steel
- **Springs:** Music wire
- **End caps:** Black polyethylene
- **Bearings:** Bronze

## DESIGN CRITERIA

- Temp range: -40°F to 150°F (-40°C to 65°C)
- Tested to UL305 & Can/ULC-S132 standard for panic devices
- Certified for doors up to 4' x 7' (width x height)
- Models available for flush through 1-5/8" offset doors
- Designed for 1/4" mounting screws



Visit [kasonind.com](http://kasonind.com) for information on the [0778](#) latch and [0779](#) strike options



Part No.*	Description	Door Thickness	Weight
10488LC225102	Panic Bar Inside Release w/ 0778 Latch and 0778 Flush Strike, 2-1/4" Wall #602 (UL)	2-1/4" (57.2 mm)	11.59 lb (5.26 kg)
10488LC225302	Panic Bar Inside Release w/ 0778 Latch and 0779 Flush Strike, 2-1/4" Wall #602 (UL)	2-1/4" (57.2 mm)	11.76 lb (5.33 kg)
10488LC400102	Panic Bar Inside Release w/ 0778 Latch and Strike, 4" Wall #602 (UL)	4" (101.6 mm)	11.59 lb (5.26 kg)
10488LC400302	Panic Bar Inside Release w/ 0778 Latch and 0779 Flush Strike, 4" Wall #602 (UL)	4" (101.6 mm)	11.76 lb (5.33 kg)

0488L Panic Bar Inside Release and Latch Assembly (UL 305 Certified)

Part Number: 10488L\*

